



Certificate for the UL Mark – Enhanced Security Performance of Doors PAS 24:2016

Section 1 – Certification details:

Customer Name:	Vista Panels Ltd	Certification Body:	UL International (UK) Ltd
Fabrication Address:	Unit H1 Prenton Way North Cheshire Trading Estate Wirral Merseyside CH43 3DU	Certification Body Address:	Halesfield 2, Telford, Shropshire, TF7 4QH United Kingdom
Certification Scheme:	Enhanced Security Performance of Doors PAS 24:2016	Certificate Number:	BP21296-3
Date of Commencement:	08/03/2019	Date of Expiry:	07/03/2025
Certificate Compiled by:	Nick Steventon Certification Auditor	Certificate Approved by:	Mark Swanborough Certification Leader
Signed:		Signed:	

Section 2 - Products covered by this certificate:

System type and configurations:

System	Range of Configurations	Opening Direction	Maximum Casement Size (WxH)
XtremeDoor Range PVC-U / Composite Doorset	Single Doorset	Inward and Outward opening leaf	914 mm x 2013 mm NOTE: Additional PVC-U edge protection is added

Extrapolation rules - Assuming identical hardware is fitted as specified in this certificate, the products listed are covered up to the maximum sizes stated above and down to a 50% reduction in height and/or width.

Section 3 - Supporting test documentation:

Initial Type Testing:

Product Type	Variant	BS 6375-1:2009	PAS 24:2016
XtremeDoor Range	Single Doorset	Test	Test
		Category	Class
		Exitex UMT / Exitex MDS83 Threshold only	800 (on largest specimen)
		Exitex MDS80/2 Threshold only	800X (on largest specimen)
		OUM4 / MXS 15/2/TB Thresholds	1200 (on largest specimen)
		Other Thresholds	800U (on largest specimen)
			Annex A&B
			D

Copyright © 2020 UL International (UK) Ltd, Unit 1-3 Horizon, Kingsland Business Park, Wade Road, Basingstoke, Hampshire RG24 8AH, UK authorizes the above named company to reproduce this Certificate only for purposes as described in the Service Terms.

Annex A – Product Details

Door Leaf		
	Part No. / Material	Dimension (mm)
Door Panel	Nan-Ya Plastics Corporation Standard Range (SBD) – 44.5mm GRP Faced Composite Door Blank DoorCo Ltd, GRP Composite 44 mm leaf Internal/External skins + reinforcing, 2mm GRP manufactured from SMC Core, polyurethane foam	46P, 48P, 68P, 00P, 6FP 2mm skins + ABS central board Refer to Min / Max sizes above Product code carries “ES” Suffix 64C: 6 Panel & 4 panel long top combo 4BT: 4 Panel Blank Top 6CT: 6 Line Cottage VFL: Vertical Flush GFL: Grooved Flush 4PA: 4 Panel Long Pre Aperture 3PA 3 Panel Sidelite 34L: ¾ Lite CFM: Craftsman PFL: Links Flush MZF: Monza Flush
Door edges	PVC-U edge banding to stiles	44 x 2 PUR Hotmelt adhesive
Rain Deflector	Exitex Rain Deflector and Exitex Rain Deflector Expelex CFNS	35 x 15 4No. 4 x 20 screws

Door Frame		
	Part No. / Material	Dimension (mm)
Head and Jambs	Eurocell Ultimate 70 (Ref: EWS 031)	70 x 80
	Eurocell Ultimate 70 (Ref: EWS 032)	70 x 65
	Eurocell Ultimate 70 (Ref: EWS 033)	70 x 85
Reinforcement	PVC-U Extrusion for EWS031 profile (Ref: EWS 831P) Location: Frame Jambs	43 x 37
	PVC-U Extrusion for EWS 032 profile (Ref:EWS 832P) Location: Frame Jambs	43 x 22
Threshold	Exitex (Inward Opening): UMT MDS70 MDS80/2 MDS83 MDS25 MDS140 MDS150 MWK R2/20 MXS15/2/TB Exitex (Outward Opening): OUM OUM/4 OUM/TD OUM125 Stormguard: (Inward Opening): AM3 Stormguard (Outward opening): AM5	-

Jointing Method	Mechanically fixed to jamb reinforcement screwports or timber stub 4.3 x 20 screws (Threshold to Sill) 4.0 x 60 screws (Sill to Jamb stub)	-
Sill	Eurocell Ultimate 70 (Ref: AC85 / BC85) - Eurocell Ultimate 70 (Ref: AC150 / BC150) Eurocell Ultimate 70 (Ref: AC180 / BC180)	85 x 30 150 x 30 180 x 30

Perimeter sealing details		
	Description / Part No. / Material	-
Frame reveal	Option 1: Central Extrusions Ref: B200 Type: Bubble gasket	-
	Option 2: Eurocell Co-extruded gasket	-
	Linear / Schlegel / Exitex Type: Brush seal	-
Seal continuity	Seals uninterrupted by hardware. Brush seal interrupted by hardware.	-

Glazing & Infill		
	Description / Part No. / Material	-
Glass Configuration	At least 1 pane must be class P1A according to BS EN 356	-
Cassette internal and external face	Nan-Ya plastics corporation clip and adhesive fixed glazing cassette system in standard styles: MAS 9V: Sunburst MAS 7B: Half Glazed Arch + Grid MAS 7D: Twin Arch MAS 9E/F: Eyebrow MAS 9W: Half Moon MAS 7A: Half Glazed Arch Top MAS 9N: Twin Vertical MAS 9Q: Half Glazed MAS 7C: Half Glazed + Grid MAS 9S: Twin tops MAS 2F: Mid panel MAS 9X: Oval MAS 9Y: Diamond MAS 7K: Centre panel (9 panel) MAS 9M: Centre panel (8 panel) MAS 7L: Low	-
Gasket	UK industrial tapes Ref: Foam 10 x 1.6 UK industrial tapes / A.E Harris & Co. Ltd Ref: Prolink 6mm / 10mm PU grip adhesive	Between leaf and cassette Cassette fixing lugs
Bead Fixings	Clip fixed	-

Glazing & Infill		
	Description / Part No. / Material	-
Glass Configuration	At least 1 pane must be class P1A according to BS EN 356	-
Cassette internal and external face	Door Co Craftsman 3 lite ODL Cassettes TriSys range Style 0806 Style 0836 Style 0836SR Style 0836ST Style 2236 Style 223609 Style 0718 Style HR01 Style HR05 Style 0824 Style 2236RT Style 223611 Style 0707 Style 0864 Style 0764 Style 0848 Style 2248 ODL Cassettes CR range Style 816 Style 817 Style 818	-
Sealants	10mm x 1.5mm Prolink 1500R Bluefilmic liner (GB10)	Between leaf/cassette and glass and cassette
Bead Fixings	Screw fixed with decorative clip fix cover	-

Hardware		
	Part No. / Material	Fixings
Cylinder	UAP (Ref: Zero Lift SXD) KM 561977 / 35/35 / YALE (Ref: Anti-Bump Cylinder) KM 532920 / 35/35 / Or an alternative cylinder and handle combination can be used that meets the requirements of PAS 24:2016 as stated below; • Cylinder certified to BS EN 1303:2015 including Cylinder Vulnerability Assessment • Cylinder certified to TS 007:2014 – 3 star level • Cylinder certified to Sold Secure – Gold level • Cylinder certified to PAS 24:2016 Annex A • Combination of handle, cylinder & cylinder protection to have a minimum combined total of 3 star rating to TS 007:2014 (e.g. 1 star cylinder + 2 star handle or 1 star cylinder + 2 star cylinder protection)	M5 machine screw
Cylinder protection	Paddock Fabrications (Ref. Cylinder guard 9101) Ingenious Locks & Hardware (Ref. Cylinder guard 6101)	M6 x 60 machine screw
Handles	Handle: Trojan Hardware & Design Ltd (Ref: Sparta) / 120 Lever / Ingenious Locks and Hardware (Ref. 4000 / 4002 series) / 120 Lever	M6 x 60 screws

Copyright © 2020 UL International (UK) Ltd, Unit 1-3 Horizon, Kingsland Business Park, Wade Road, Basingstoke, Hampshire RG24 8AH, UK authorizes the above named company to reproduce this Certificate only for purposes as described in the Service Terms.

	Total Hardware (Ref: Quantum / Endurance) / 120 Lever Yale, TS007 2* Door pull (Polished chrome), code: YLKTCP	
Locking Mechanism	Option 1: Paddock Fabrications (Ref: PL147-45-03) 45 wide Option 2: YALE / Millenco / Assa Abloy (Ref: Mantis 3 MA80073) (Full faceplate) 40 wide Option 3: YALE / Millenco / Assa Abloy (Ref: Mantis 3 MA85030) (20mm faceplate) 20 wide Option 4: Ingenious Locks & Hardware (Ref. 1009 5 hook MPL) 20 wide Option 5: Winkhaus AV2-F 2070/45 92/8 M2 (L/H and R/H) 20 wide Option 6: Winkhaus, AV2 Heritage 2070/55, code: 5008984 L/H and 5008982 R/H. Option 7: Ingenious Locks & Hardware 3 Latch Heritage 45mm Backset Autofire Lock 1044 with CPG Gimlet Point fixing	4.3 x 32 screws into leaf
Hinges	MILA Hardware (Ref: iDeal Butt Hinge 22260) 100 x 30 ERA (Ref. Challenger 3D Butt Hinge) 100 x 50 Winkhaus ECO Hinge 102 x 35 SFS 2D adjustable Butt Hinge 9016 Dynamic 2D Nico Manufacturing White Icon Adjustable Hinge	5.0 x 60 screws to Frame 4.5 x 40 screws to Leaf
Keeps	Option 1: Paddock Fabrications (Ref: PLK481-19 Keep set) Option 2/3: YALE / Millenco / Assa Abloy (Ref: Mantis 3 keep set) Option 4: Ingenious Locks & Hardware (Ref. 1146) Option 5: Winkhaus AV2 F24 908W R/End MV1 Winkhaus F24-908W R/End U Option 6: 2No. F24 908W AV2 MV1 R/End keeps FX4 (Silver), code: 4933948. 1No. F24-908W Centre keeps R/End U (Silver), code: 4937126 L/H and 4937125 R/H.	4.2 x 45 screws into frame 4.2 x 45 screws into frame 4.2 x 45 screws into frame 4.3 x 32 screws into frame
Letter plate	Trojan 0793 TS008 Letterplate Or alternative letterplate may be used that meets the requirements of TS008:2015 - Enhanced security grade 2	-